




GIGANET[®]
COMMUNICATIONS

**FICHA TÉCNICA
GFO-091 Y GFO-093
DE 6 A 12 HILOS**

1. Cable Construction

1.1 Cable cross-section



2. Cable Specification

2.1 Sheath marking

KXOFC	2022	GYXTW	XXB1.3 (G.652D)	XXXXm
KXOFC	: Manufacturer's brand			
2022	: Manufacture year			
GYXTW	: Cable type			
XXB1.3 (G.652D)	: XX cores single-mode optical fiber (ITU-T Rec. G.652D)			
XXXXm	: Mark of meters			
*The marking is printed every 1 meter;				
***"G.652D" means ITU-T Rec. Low Water Peak (LWP) G.652 Single Mode Optical Fiber.				

2.2 The color of marking is white, but if the remarking is necessary.

2.3 An occasional unclear of length marking is permitted if both of the neighboring markings are clear;

2.4 The both cable ends are sealed with heat shrinkable end caps to prevent water ingress.

2.5 Fiber color code

No.	1	2	3	4	5	6
Color	Blue	Orange	Green	Brown	Gray	White
No.	7	8	9	10	11	12
Color	Red	Black	Yellow	Violet	Pink	Aqua

2.6 Color Code for Loose Tube (LT) & Filler Rod (FR)

Fiber count	Element no., name & color code					
	1	2	3	4	5	6
12	LT	/	/	/	/	/

* "LT" means "Loose tube";

** "FR" means "Filler rod";

2.7 Cable structure and parameter

Items		unit	Details
Optical fiber	Type		Single Mode G.652.D
Loose tube	Material		PBT
	Diameter	mm	2.0
Strength member	Material		Two Steel wire
	Diameter	mm	0.7mm
Armor	Material	mm	Corrugated steel tape
Sheath	Material		MDPE
	Diameter	mm (±0.3)	7.0
Tension		N	600/1500
Crush		N/100mm	300/1000

* The nominal sheath thickness may vary by ±0.2mm.

** The nominal outer diameter and height may vary by ±0.3mm.

3. Fiber Properties

3.1 The properties of single mode optical fiber (ITU-T Rec. G.652D)

Item	Specification
Fiber type	Single mode
Fiber material	Doped silica
Attenuation coefficient @ 1310 nm	≤ 0.36 dB/km

@ 1383 nm	≤ 0.32 dB/km
@ 1550 nm	≤ 0.22 dB/km
@ 1625 nm	≤ 0.30 dB/km
Point discontinuity	≤ 0.05 dB
Cable cut-off wavelength	≤ 1260 nm
Zero-dispersion wavelength	1300 ~ 1324 nm
Zero-dispersion slope	≤ 0.093 ps/(nm ² .km)
Chromatic dispersion	
@ 1288 ~ 1339 nm	≤ 3.5 ps/(nm. km)
@ 1271 ~ 1360 nm	≤ 5.3 ps/(nm. km)
@ 1550 nm	≤ 18 ps/(nm. km)
@ 1625 nm	≤ 22 ps/(nm. km)
PMD _Q (Quadrature average*)	≤ 0.2 ps/km ^{1/2}
Mode field diameter @ 1310 nm	9.2±0.4 μ m
Core / Clad concentricity error	≤ 0.5 μ m
Cladding diameter	125.0 ± 0.7 μ m
Cladding non-circularity	$\leq 1.0\%$
Primary coating diameter	245 ± 10 μ m
Proof test level	100 kpsi (=0.69 Gpa), 1%
Temperature dependence 0°C~ +70°C @ 1310 & 1550nm	≤ 0.1 dB/km

* PMD_Q is a link of 20 cable sections (M) and a probability level of 0.01% (Q).

4. Characteristic of Optical Cable

4.1 Mechanical & environmental characteristics

4.1.1 Cable bending radius: 10 x cable diameter (during operation)

20 x cable diameter (during installation)

4.1.2 Temperature range and humidity

Operating temperature range	-40°C to +60°C
Storage / Transport temperature range	-50°C to +70°C
Installation temperature range	-20°C to +50°C

4.2 Main mechanical & environmental characteristics test

NO	ITEM	TEST METHOD	ACCEPTANCE REQUIREMENTS
1	Tensile Strength IEC 794-1-E1	- Load: 1,500 N - Length of cable under load: 50m - Load time: 5 min.	- Loss change ≤ 0.1 dB @1550 nm - No fiber break and no sheath damage.

2	Crush Test IEC 60794-1-E3	- Load: 1, 000 N/100mm - Load time: ≥1min	- Loss change ≤ 0.1 dB @1550 nm - No fiber break and no sheath damage.
3	Impact Test IEC 60794-1-E4	- Points of impact: 5 - Times of per point: 5 - Impact energy: 4.5 Nm - Radius of hammer head: 12.5mm - Impact rate: 2sec/cycle	- Loss change ≤ 0.1 dB @1550 nm - No fiber break and no sheath damage.
4	Repeated Bending IEC 60794-1-E6	- Bending Dia.: 20 x OD - Load: 150N - Flexing rate: 3sec/cycle - No. of cycle: 30	- Loss change ≤ 0.1 dB @1550 nm - No fiber break and no sheath damage.
5	Torsion IEC 60794-1-E7	- Length: 1m - Load: 150N - Twist rate: 1min/cycle - Twist angle: ±180° - No. of cycle: 10	- Loss change ≤ 0.1 dB @1550 nm - No fiber break and no sheath damage.
6	Water Penetration IEC 60794-1-F5B	- Height of water: 1m - Sample length: 3 m - Time: 24 hour	- No water shall have leaked from the opposite end of cable
7	Temperature Cycling IEC 60794-1-F1	- Temperature step: +20°C→-10°C→+70°C →+20°C - Time per each step: 12 hrs - Number of cycle: 2	- Loss change ≤ 0.1 dB @1550 nm - No fiber break and no sheath damage.
8	Compound Flow IEC 60794-1-E14	- Sample length: 30 cm - Temp: 70°C ± 2°C - Time: 24 hours	- No compound flow